

## Brik drill results 2011

Hole ID	From(m)	To(m)	Int(m)	Au ppm	From(ft)	To(ft)	Int(ft)	OPT Au
PB01	44.1	50.2	6.1	0.25	145	165	20	0.007
PB02				NSV				
PB03	70.0	73.0	3.0	0.30	230	240	10	0.009
PB04	42.6	47.2	4.6	0.40	140	155	15	0.012
PB05	28.9	30.4	1.5	0.32	95	100	5	0.009
PB06				NSV				
PB07	No Significant Values							
PB08	No Significant Values							
PB09	No Significant Values							
PB10	51.7	53.2	1.5	0.37	170	175	5	0.011
PB11	No Significant Values							
PB12	No Significant Values							
PB13	No Significant Values							
PB14	No Significant Values							
PB15	53.2	57.8	4.6	0.41	175	190	15	0.012
PB16	6.1	13.7	7.6	1.00	20	45	25	0.029
PB17	0.0	19.8	19.8	1.30	0	65	65	0.038
PB18	No Significant Values							
PB19	24.3	27.4	3.0	0.46	80	90	10	0.013
and	47.2	57.8	10.6	0.98	155	190	35	0.029
PB20	25.9	30.4	4.6	0.60	85	100	15	0.017
PB21	No Significant Values							
PB22	No Significant Values							
PB23	No Significant Values							
PB24	0.0	18.3	18.3	0.99	0	60	60	0.029
incl	4.6	7.6	3.0	2.81	15	25	10	0.082
and	30.4	35.0	4.6	0.23	100	115	15	0.007
and	53.2	60.8	7.6	0.28	175	200	25	0.008
and	98.9	115.6	16.7	2.41	325	380	55	0.070
incl	103.4	104.9	1.5	14.95	340	345	5	0.436
PB25	0.0	35.0	35.0	0.82	0	115	115	0.024
PB26	No Significant Values							
PB27	No Significant Values							

Intervals were calculated using a 0.20 g/t cut-off and maximum 3 m of internal waste.

True thickness of intercepts varies, but in most cases is believed to represent 70 to 80% of true thickness, as holes were angled across mineralized structures. Pilot Gold employs a rigorous quality control system by inserting a blank, standard or duplicate into the sample stream for every 10 drill samples. All gold values reported are 30 gram Fire Assay with Atomic Absorption finish. All assays were performed by ALS Chemex at their Reno and Vancouver labs following preparation in the Elko lab.