

Cutoff (g/t)	0.2, 0.5, 1.0, 5.0
Min g/t*m	1.0
Max Waste (m)	5.0
Topcut (g/t)	100.0

Liberty Gold - Goldstrike 2018 Current Drill Holes

Hole ID (Az, Dip) (degrees)	From (m)	To (m)	Intercept (m)	Au (g/t)	Au Cut-Off	Hole Length (m)	Target	Comments	g/t x m
PGS518 (272, -50)			NSR			129.5	Peg Leg		
PGS520 (225, -50)			NSR			182.9	Peg Leg		
PGS522 (50, -50)	118.9	123.4	4.6	0.27	0.2	152.4	Peg Leg		1.2
PGS557 (90, -65)			NSR			99.1	Peg Leg		
PGS559 (180, -60)	64.0	67.1	3.0	0.58	0.2	138.7	Peg Leg		
PGS562 (270, -50)	140.2	152.4	12.2	1.07	0.2	190.5	Peg Leg		13.1
PGS563 (100, -60)	7.6	18.3	10.7	0.36	0.2	82.3	Peg Leg		3.9
PGS567 (305, -65)	3.0	7.6	4.6	0.71	0.2	51.8	Peg Leg		16.8
and	19.8	21.3	1.5	8.85					
PGS568 (65, -78)	88.4	93.0	4.6	0.75	0.2	126.5	Peg Leg		3.4
PGS570 (65, -45)	48.8	50.3	1.5	0.33	0.2	61.0	Peg Leg		0.5
PGS571 (95, -60)	16.8	19.8	3.0	0.37	0.2	79.3	Peg Leg		1.1
PGS573 (270, -50)			NSR			61.0	Peg Leg		
PGS574 (230, -70)	57.9	103.6	45.7	0.79	0.2	141.7	Peg Leg		36.3
incl	61.0	71.6	10.7	1.88	1				
PGS575 (140, -63)	24.4	44.2	19.8	0.31	0.2	121.9	Peg Leg		6.2
PGS577 (145, -45)	0.0	16.8	16.8	0.48	0.2	144.8	Peg Leg		34.1
and	96.0	132.6	36.6	0.71					
PGS579 (120, -45)	0.0	32.0	32.0	0.44	0.2	121.9	Peg Leg		62.7
and	77.7	120.4	42.7	1.14	0.2				
incl	100.6	118.9	18.3	2.00	1				
PGS580 (320, -53)	41.1	83.8	42.7	0.57	0.2	129.5	Peg Leg		31.4
incl	62.5	65.5	3.0	3.43	1				
and	86.9	100.6	13.7	0.52	0.2				
PGS582 (120, -60)	3.0	7.6	4.6	0.47	0.20	105.16	Peg Leg		9.4
and	13.7	25.9	12.2	0.60					

Hole ID (Az, Dip) (degrees)	From (m)	To (m)	Intercept (m)	Au (g/t)	Au Cut-Off	Hole Length (m)	Target	Comments	g/t x m
PGS619 (310, -65)			NSR			86.9	Peg Leg		
PGS621 (90, -70)			NSR			121.9	Peg Leg		
PGS622 (50, -60)	106.7	109.7	3.0	0.36	0.2	152.4	Peg Leg		1.1
PGS624 (45, -80)			NSR			111.252	Peg Leg		
PGS626 (190, -55)	0.0	13.7	13.7	0.54	0.2	147.828	Peg Leg		16.9
and	99.1	105.2	6.1	0.55					
and	123.4	135.6	12.2	0.51					
PGS628 (60, -75)	0.0	12.2	12.2	0.61	0.2	140.2	Peg Leg		11.3
and	21.3	24.4	3.0	0.28					
and	68.6	71.6	3.0	0.30					
and	86.9	91.4	4.6	0.28					
and	109.7	111.3	1.5	0.49					
PGS629 (70, -65)			NSR			147.8	Peg Leg	L Peg Leg	
PGS630 (60, -75)	39.6	106.7	67.1	1.17	0.2	129.54	Peg Leg		78.3
incl	51.8	77.7	25.9	2.21	1.0				
PGS631 (0, -75)	44.2	96.0	51.8	0.99	0.2	120.4	Peg Leg		59.7
incl	74.7	85.3	10.7	2.45	1.0				
and	105.2	109.7	4.6	1.84	0.2				
PGS632 (255, -50)			NSR			178.3	Peg Leg	L Peg Leg	
PGS634 (180, -75)	57.9	97.5	39.6	0.65	0.2	135.6	Peg Leg		25.6
PGS636 (180, -70)	0.0	9.1	9.1	1.63	0.2	141.7	Peg Leg		51.4
and	12.2	16.8	4.6	0.20					
and	68.6	73.2	4.6	0.38					
and	79.2	100.6	21.3	1.59					
PGS638 (290, -75)	0.0	9.1	9.1	0.80	0.2	152.4	Peg Leg		12.8
and	15.2	24.4	9.1	0.37					
and	134.1	138.7	4.6	0.47					