

Cutoff (g/t)	0.2, 1.0, 5.0
Min g/t*m	1.0
Max Waste (m)	5.0

Liberty Gold - Black Pine 2021 Drilling Current Release

Hole ID (Az, Dip) (degrees)	From (m)	To (m)	Intercept (m)	Au (g/t)	Au Cut-Off	Hole Length (m)	Target	Comments	g/t x m
LBP382 (165, -45)	3.1	7.6	4.6	0.31	0.20	190.5	Back Range	Step Out	34.9
and	25.9	36.6	10.7	0.63					
including	32.0	33.5	1.5	1.73	1.00				
and	42.7	71.6	29.0	0.54	0.15				
including	42.7	48.8	6.1	0.23	0.20				
including	51.8	71.6	19.8	0.70					
and including	56.4	59.4	3.0	1.23	1.00				
and	80.8	94.5	13.7	0.30	0.15				
including	89.9	94.5	4.6	0.54	0.20				
and	125.0	132.6	7.6	0.92	0.20				
including	125.0	128.0	3.0	1.37	1.00				
LBP390 (320, -45)	No Significant Results					160.0	Back Range	Step-Out	
LBP395 (255, -45)	13.7	21.3	7.6	0.22	0.15	152.4	Back Range	Step-Out	39.8
and	59.4	99.1	39.6	0.41					
including	59.4	86.9	27.4	0.50	0.20				
and	88.4	99.1	10.7	0.24					
and	105.2	112.8	7.6	1.44	1.00				
including	105.2	108.2	3.0	2.29					
including	109.7	111.3	1.5	1.16	0.20				
and	129.5	132.6	3.0	0.34					
and	144.8	152.4	7.6	1.30*	1.00				
including	146.3	150.9	4.6	1.94*					
LBP398 (265, -60)	53.3	79.3	25.9	0.39	0.20	147.8	Back Range	Step-Out	14.4
and	88.4	94.5	6.1	0.39	0.15				
including	88.4	93.0	4.6	0.46	0.20				
and	103.6	108.2	4.6	0.41	0.20				
LBP400 (85, -75)	6.1	9.1	3.0	0.54	0.20	190.5	Back Range	Step-Out	46.8
and	27.4	56.4	29.0	1.01	0.15				
including	33.5	56.4	22.9	1.22	0.20				
and including	41.2	54.9	13.7	1.66	1.00				
and	96.0	114.3	18.3	0.87*	0.15				
including	99.1	112.8	13.7	1.10*	0.20				
and including	100.6	109.7	9.1	1.42*	1.00				

*reduced cyanide solubility in this interval