

Liberty Gold - Black Pine Drill Holes

Hole ID (Az, Dip) (degrees)	From (m)	To (m)	Intercept (m)	Au (g/t)	Au Cut-Off	Hole Length (m)	Target	g/t x m
LBP929 (210, -60)	7.6	16.8	9.1	0.31		294.1	Discovery	43.8
and	18.3	29.0	10.7	0.17	0.15			
and	44.2	93.0	48.8	0.72				
including	80.8	88.4	7.6	2.55	1.00			
and	152.4	160.0	7.6	0.24	0.15			
and	205.7	214.9	9.1	0.27				
LBP933 (250, -50)	47.2	51.8	4.6	0.39		184.4	Back Range	2.8
and	65.5	70.1	4.6	0.23	0.15			
LBP934 (290, -50)	0.0	4.6	4.6	0.23		233.2	Discovery	24.4
and	27.4	68.6	41.1	0.30				
and	74.7	89.9	15.2	0.28	0.15			
and	149.4	164.6	15.2	0.19				
and	167.6	178.3	10.7	0.20				
and	222.5	227.1	4.6	0.38				
LBP935 (160, -50)	16.8	25.9	9.1	0.41	0.15	214.9	Back Range	5.2
including	22.9	24.4	1.5	1.11	1.00			
and	33.5	35.1	1.5	0.95	0.15			
LBP936 (230, -45)	0.0	3.0	3.0	0.39		281.9	Discovery	23.0
and	36.6	51.8	15.2	0.32				
and	57.9	64.0	6.1	0.52	0.15			
and	131.1	141.7	10.7	0.35				
and	164.6	173.7	9.1	0.41				
and	199.6	219.5	19.8	0.25				
and	222.5	230.1	7.6	0.17				
LBP937 (0, -80)	7.6	18.3	10.7	0.34	0.15	129.5	Back Range - Reduced AUCN	3.6
LBP938 (0, -45)	16.8	32.0	15.2	0.37		196.6	Back Range	38.2
and	38.1	76.2	38.1	0.86	0.15			
including	50.3	59.4	9.1	2.12				
including	62.5	64.0	1.5	1.31	1.00			
LBP939 (0, -90)	44.2	50.3	6.1	0.30		274.3	Discovery	12.6
and	138.7	141.7	3.0	0.82	0.15			
and	167.6	179.8	12.2	0.68				
including	173.7	176.8	3.0	1.57	1.00			
LBP940 (150, -45)	7.6	10.7	3.0	0.87	0.15	91.4	Back Range - Reduced AuCN	8.3
including	9.1	10.7	1.5	1.18	1.00			
and	64.0	70.1	6.1	0.93	0.15			
including	65.5	67.1	1.5	1.03	1.00			
LBP942 (15, -45)	73.2	85.3	12.2	0.76	0.15	152.4	Back Range - Reduced AuCN	23.7
including	74.7	76.2	1.5	1.17	1.00			
and	91.4	118.9	27.4	0.52	0.15			
including	94.5	96.0	1.5	1.32	1.00			
LBP943 (90, -45)	9.1	18.3	9.1	0.49		114.3	Back Range	38.3
and	35.1	38.1	3.0	0.51	0.15			
and	79.2	102.1	22.9	1.41				
including	82.3	88.4	6.1	4.28	1.00			
and including	83.8	85.3	1.5	8.45	5.00			
LBP944 (160, -58)	29.0	59.4	30.5	0.62	0.15	249.9	Discovery	30.2
including	33.5	35.1	1.5	1.02				
including	39.6	41.1	1.5	1.48	1.00			
and	80.8	85.3	4.6	0.26	0.15			
and	89.9	96.0	6.1	0.92				
including	91.4	94.5	3.0	1.66	1.00			
and	121.9	125.0	3.0	0.59				
and	158.5	166.1	7.6	0.17	0.15			
and	211.8	216.4	4.6	0.30				
LBP945 (270, -45)	0.0	51.8	51.8	0.36	0.15	152.4	Back Range	132.7
including	13.7	16.8	3.0	1.37	1.00			
and	74.7	106.7	32.0	3.40	0.15			
including	74.7	102.1	27.4	3.88	1.00			
and including	79.2	88.4	9.1	6.74	5.00			
and	126.5	134.1	7.6	0.72	0.15			
including	128.0	131.1	3.0	1.22	1.00			

Hole ID (Az, Dip) (degrees)	From (m)	To (m)	Intercept (m)	Au (g/t)	Au Cut-Off	Hole Length (m)	Target	g/t x m
LBP947 (20, -70)	0.0	16.8	16.8	0.31		181.4	Back Range - Reduced AUCN below 108 m	40.9
and	30.5	33.5	3.0	0.43	0.15			
and	51.8	62.5	10.7	0.56				
including	54.9	56.4	1.5	1.06	1.00			
and	77.7	109.7	32.0	0.55	0.15			
including	88.4	89.9	1.5	1.79				
including	96.0	97.5	1.5	2.07	1.00			
including	106.7	108.2	1.5	1.08				
and	120.4	128.0	7.6	0.43	0.15			
including	121.9	123.4	1.5	1.13	1.00			
and	138.7	143.3	4.6	0.39				
and	152.4	157.0	4.6	0.87	0.15			
including	152.4	153.9	1.5	1.68	1.00			
and	166.1	172.2	6.1	0.32	0.15			
LBP948 (0, -90)	76.2	94.5	18.3	0.17		274.3	Discovery	9.2
and	112.8	121.9	9.1	0.21	0.15			
and	143.3	149.4	6.1	0.27				
and	176.8	185.9	9.1	0.28				
LBP949 (0, -45)	No Significant Results					141.7	Back Range	
LBP951 (270, -45)	44.2	56.4	12.2	0.53		99.1	Back Range - Reduced AuCN	8.8
and	65.5	71.6	6.1	0.39	0.15			
LBP952 (180, -60)	38.1	50.3	12.2	0.87	0.15	152.4	Back Range	10.6
including	42.7	45.7	3.0	1.73	1.00			
LBP953 (0, -90)	62.5	83.8	21.3	0.30		231.6	Discovery	12.7
and	102.1	112.8	10.7	0.60	0.15			
including	103.6	105.2	1.5	1.47	1.00			
LBP955 (120, -50)	0.0	4.6	4.6	0.54		182.9	Back Range - Reduced AUCN	55.2
and	18.3	22.9	4.6	0.23	0.15			
and	50.3	59.4	9.1	0.68				
including	54.9	57.9	3.0	1.15	1.00			
and	149.4	182.9	33.5	1.36	0.15			
including	176.8	182.9	6.1	3.32	1.00			
LBP957 (75, -45)	19.8	70.1	50.3	0.37		205.7	Back Range	53.6
and	73.2	149.4	76.2	0.41	0.15			
including	140.2	144.8	4.6	1.97	1.00			
and	153.9	161.5	7.6	0.44	0.15			
LBP959 (240, -45)	3.0	7.6	4.6	0.32		129.5	Back Range	6.1
and	59.4	67.1	7.6	0.61	0.15			
including	65.5	67.1	1.5	1.29	1.00			